



All dimensions are in millimeters, Strength values are in kg-f

Part No.	Rivet Ø	Hole Ø	Grip Range	D	k	L	Shear strength	Tensile strength
CEUU32020D	3.2	3.3–3.5	0.5–2.0	6.0	1.3	6.0	204 kg-f (2001 N)	255 kg-f (2501 N)
CEUU32040D			2.0–4.0			8.0		
CEUU32060D			4.0–6.0			10.0		
CEUU32080D			6.0–8.0			12.0		
CEUU32100D			8.0–10.0			14.0		
CEUU32120D			10.0–12.0			16.0		
CEUU32130D			11.0–13.0			17.0		
CEUU40015D	4.0	4.1–4.3	0.5–1.5	8.0	1.6	6.0	306 kg-f (3001 N)	408 kg-f (4001 N)
CEUU40035D			1.5–3.5			8.0		
CEUU40055D			3.5–5.5			10.0		
CEUU40085D			6.5–8.5			13.0		
CEUU40115D			9.5–11.5			16.0		
CEUU40135D			11.5–13.5			18.0		
CEUU48030D	4.8	4.9–5.1	1.0–3.0	9.5	1.8	8.0	459 kg-f (4501 N)	561 kg-f (5502 N)
CEUU48050D			3.0–5.0			10.0		
CEUU48070D			5.0–7.0			12.0		
CEUU48090D			7.0–9.0			14.0		
CEUU48110D			9.0–11.0			16.0		
CEUU48130D			11.0–13.0			18.0		
CEUU48150D			13.0–15.0			20.0		
CEUU48170D			15.0–17.0			22.0		
CEUU48200D			18.0–20.0			25.0		

BODY MATERIAL	Stainless Steel Grade (Polished)
MANDREL MATERIAL	Stainless Steel Grade (Polished)