



All dimensions are in millimeters. Strength values are in Newtons (N)

Part No.	Rivet Ø	Hole Ø	Grip Range	D (max)	k (max)	L	Qty/Pod
TE304DB	2.4	2.49-2.55	0.00-1.50	4.2	0.9	3.2	
TE306DB			1.60-3.10			4.8	
TE308DB			3.20-4.70			6.4	
TE310DB			4.80-6.30			7.9	
TE404DB	3.2	3.28 - 3.34	0.00-1.50	5.5	1.2	3.2	
TE406DB			1.60-3.10			4.8	
TE408DB			3.20-4.70			6.4	
TE410DB			4.80-6.30			7.9	
TE506DB	4.0	4.09 - 4.16	1.60-3.10	6.5	1.5	4.8	
TE508DB			3.20-4.70			6.4	
TE510DB			4.80-6.30			7.9	
TE512DB			6.40-7.90			9.5	
TE514DB			8.00-9.50			11.1	
TE607DB	4.8	4.85 - 4.93	1.60-3.10	8.9	1.8	5.6	
TE609DB			3.20-4.70			7.2	
TE611DB			4.80-6.30			8.8	
TE613DB			6.40-7.90			10.3	
TE615DB			8.00-9.50			11.9	

STRENGTH VALUES

Diameter Ø	Steel	Aluminium	Brass
2.4	-	300 N (31 kg-f)	800 N (82 kg-f)
3.2	1400 N (143 kg-f)	600 N (61 kg-f)	1300 N (133 kg-f)
4.0	2400 N (245 kg-f)	1000 N (102 kg-f)	2300 N (235 kg-f)
4.8	3200 N (326 kg-f)	1500 N (153 kg-f)	3100 N (316 kg-f)