



All dimensions are in millimeters

Part No.	A	Hole size	Grip range	B	C	D	Thread size	Tightening Torque (KGf/CM)	Hardness (+/-5)
TRNN03126	7.9	7.9-8.2	0.40-4.0	12.60	1.20	11.00	M3 x 0.50	2.5-5.0	60
TRNN03249	7.9	7.9-8.2	9.50-13.0	24.90	0.90	14.00	M3 x 0.50	2.5-5.0	60
TRNN04126	7.9	7.9-8.2	0.40-4.0	12.60	1.40	11.00	M4 x 0.70	2.5-4.0	70
TRNN04142	7.9	7.9-8.2	0.40-4.4	14.20	1.50	19.05	M4 x 0.70	2.5-4.0	70
TRNN04240	7.9	7.9-8.2	8.50-15.0	24.00	1.20	11.00	M4 x 0.70	2.5-4.0	65
TRNN05110	9.6	9.6-9.8	0.50-1.5	11.00	1.50	12.70	M5 x 0.80	3.5-5.0	65
TRNN05141	9.6	9.6-9.8	0.40-4.9	14.10	0.90	12.70	M5 x 0.80	3.5-5.0	60
TRNN05170	9.6	9.6-9.8	0.85-5.9	17.00	1.00	14.00	M5 x 0.80	3.0-7.0	60
TRNN05180	9.6	9.6-9.8	0.80-5.8	18.00	2.00	19.00	M5 x 0.80	3.0-7.0	60
TRNN05209	9.6	9.6-9.8	0.80-5.8	20.95	4.70	18.95	M5 x 0.80	4.0-7.0	60
TRNN05195	9.6	9.6-9.8	0.80-5.8	19.50	4.70	14.00	M5 x 0.80	4.0-7.0	60
TRNN05215	9.6	9.6-9.8	7.90-11.4	21.50	0.90	14.00	M5 x 0.80	3.0-9.0	60
TRNN05265	9.6	9.6-9.8	7.90-16.0	26.50	1.30	14.00	M5 x 0.80	3.0-7.0	60
TRNN05390	9.6	9.6-9.8	20.50-30.0	39.00	1.30	14.00	M5 x 0.80	6.0-10.0	60
TRNN05440	9.6	9.6-9.8	25.00-32.0	44.00	1.20	14.00	M5 x 0.80	6.0-10.0	60
TRNN06160	12.7	12.7-12.9	0.40-2.8	16.00	1.30	16.00	M6 x 1.00	6.0-10.0	60
TRNN06211	12.7	12.7-12.9	0.80-4.7	21.10	4.75	19.05	M6 x 1.00	8.0-10.0	70
TRNN06267	12.7	12.7-12.9	6.40-11.5	26.70	2.00	16.30	M6 x 1.00	8.0-10.0	70
TRNN06350	13.0	13.0-13.2	11.50-23.0	35.00	1.30	16.00	M6 x 1.00	8.0-10.0	65
TRNN06500	12.7	12.7-12.9	26.00-38.0	50.00	1.30	16.00	M6 x 1.00	8.0-10.0	65
TRNN08183	15.9	15.9-16.1	0.40-4.0	18.30	3.20	21.50	M8 x 1.25	10.0-15.0	60
TRNN08279	15.9	15.9-16.1	3.95-9.5	27.90	5.70	21.50	M8 x 1.25	10.0-16.0	60
TRNN08300	18.0	18.0-18.2	2.00-18.0	30.00	2.00	20.50	M8 x 1.25	10.0-16.0	60
TRNN08500	18.0	18.0-18.2	15.00-39.0	50.00	1.60	20.00	M8 x 1.25	30.0-40.0	65
TRNN10240	20.0	20.0-20.2	2.50-3.5	24.00	3.00	25.00	M10 x 1.50	45.0-55.0	60
TRNN10270	19.05	19.1-19.2	0.38-11.1	27.00	4.75	29.50	M10 x 1.50	45.0-55.0	65
TRNN12265	24.0	24.0-24.2	2.50-3.50	26.50	3.00	27.00	M12 x 1.75	60.0-70.0	65

Parts are also available for Standard in imperial threads.