


TF™ LOCKBOLT COLLARS

STANDARD

Material: Steel
Finish: Zinc Plated




All dimensions are in millimeters.

Part No.	Diameter Ref.	O.D.	I.D.	H	T	F.D.
LCSS-16G	1/2"	19.7–20.3	13.1–13.7	15.5–16.4	-	-
LCSS-20G	5/8"	24.6–25.7	16.5–16.9	21.5–22.2	-	-
LCSS-24G	3/4"	29.6–30.0	19.7–20.1	23.6–24.4	-	-
LCSS-28G	7/8"	34.2–34.9	23.1–23.7	27.5–28.3	-	-
LCSS-32G	1"	39.0–40.0	26.0–26.7	31.2–32.4	-	-
LCSS-36G	1-1/8"	44.2–45.0	29.2–30.0	35.2–36.2	-	-
LCSS-44G	1-3/8"	54.5–54.7	35.9–36.1	44.2–45.2	-	-

FLANGED

Material: Steel
Finish: Zinc Plated



All dimensions are in millimeters.

Part No.	Diameter Ref.	O.D.	I.D.	H	T	F.D.
LCFS-16	1/2"	20.1–20.5	13.1–13.6	18.2–18.9	2.4–4.0	24.6–26.2
LCFS-20	5/8"	24.6–25.7	16.5–16.9	23.6–24.4	3.2–4.7	30.9–32.5
LCFS-24	3/4"	29.6–30.5	19.7–20.1	28.4–29.1	4.0–5.5	37.3–38.9
LCFS-28	7/8"	34.2–34.9	23.1–23.7	33.0–33.8	4.7–6.4	39.7–41.3
LCFS-32	1"	39.4–40.0	26.0–26.7	37.7–38.5	5.5–7.1	46.8–48.4
LCFS-36	1-1/8"	44.2–45.0	29.2–30.0	42.4–43.2	6.4–7.9	53.2–54.8

NOTE:

When using LCFS Collars (Flange Type) include "T" dimensions as part of the total material thickness to determine the correct lockbolt pin grip number.